## MACS-007801-0M1RM0

# Mono Doppler Transceiver 24.125 GHz

#### Features

- Low Cost
- Compact Size
- Gold Plated Solder Pins
- Rugged Die cast Construction
- 10Hz to 5000Hz IF Bandwidth
- Lead Free (RoHS Compliant)

#### **Description and Applications**

M/A-COM's MACS-007801-0M1RM0 is a RoHS Compliant K-Band Mono Transceiver consisting of a Gunn Diode oscillator and Schottky Diode assembled into a die cast waveguide package. These Mono Transceivers are well suited for high volume applications where small size and reliability are required. Typical applications include police radar and presence sensing applications.

Parameter	Test Con- ditions	Units	Min.	Тур.	Max.
Operating Frequency	+25 °C	GHz	24.100	24.125	24.150
Output Power	+25 °C	mW	5.0		
Operating Current	+25 ⁰C	mA	60	85	100
Operating Voltage	+25 ⁰C	VDC		5.0	
Schottky Diode Noise	+25 ⁰C	micro- Volts		2.5	5.0
Transceiver Sensitivity	+25 ⁰C	-dBc	-93	-103	

#### **Product Specifications**

Operating temperature to full specification -30°C to +70°

#### Absolute Maximum Ratings<sup>1</sup>

Parameter	Maximum Ratings		
Operating Temperature	-40 °C to +85 °C		
Storage Temperature	-65 °C to +150 °C		
Incident RF Input Power	+20 dBm		
DC Input (Gunn Diode)	+5.5VDC		
Soldering Temperature	+260 °C max.		

1. Exceeding these limits may cause permanent damage.

1

#### Note: Device is ESD Sensitive. Proper ESD Precautions should be used when handling this Device..

ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed. PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples me or not to are may be available. Commitment to produce in volume is not guaranteed.



Rev. V4


#### **Package Outline**



#### **PIN Configuration**

PIN	Function	
1	DC Input	
2	GND	
3	IF Output	

#### **Functional Block Diagram**



North America Tel: 800.366.2266
Europe Tel: +353.21.244.6400
India Tel: +91.80.43537383
Visit www.macomtech.com for additional data sheets and product information.

Visit www.macomtech.com for additional data sheets and product informatic


y be available. MA-COM Technology Solutions nor and its diffiliates reserve the right to make changes to the product soluri ormation contained herein without notice.


## MACS-007801-0M1RM0




### Mono Doppler Transceiver 24.125 GHz

Rev. V4





2



ADVANCED: Data Sheets contain information regarding a product M/A-COM Technology Solutions is considering for development. Performance is based on target specifications, simulated results, and/or prototype measurements. Commitment to develop is not guaranteed.
PRELIMINARY: Data Sheets contain information regarding a product M/A-COM Technology Solutions has under development. Performance is based on engineering tests. Specifications are typical. Mechanical outline has been fixed. Engineering samples more to the arm by bravialable. Commitment to produce in volume is not guaranteed.
North America Tel: 800.366.2266
Europe Tel: +353.21.244.6400
India Tel: +91.80.43537383
China Tel: +86.21.2407.1588
Visit www.macomtech.com for additional data sheets and product information. Specifications are typical. Mechanical outline has been fixed. Engineering samples more to the arm by bravialable. Commitment to produce in volume is not guaranteed.