

# FG4000BX-90DA

HIGH POWER INVERTER USE  
PRESS PACK TYPE


FG4000BX-90DA



- ITQRM Repetitive controllable on-state current ..... 3000A
- IT(AV) Average on-state current ..... 1000A
- VDRM Repetitive peak off state voltage ..... 4500V
- Anode short type

OUTLINE DRAWING

Dimensions in mm



## APPLICATION

Inverters, D.C. choppers, Induction heaters, D.C. to D.C. converters.

[www.BDTIC.com/MITSUBISHI](http://www.BDTIC.com/MITSUBISHI)

## MAXIMUM RATINGS

Symbol	Parameter	Voltage class		Unit
		90DA		
VRRM	Repetitive peak reverse voltage	19		V
VRSM	Non-repetitive peak reverse voltage	19		V
VR(DC)	DC reverse voltage	19		V
VDRM	Repetitive peak off-state voltage <sup>+</sup>	4500		V
VDSM	Non-repetitive peak off-state voltage <sup>+</sup>	4500		V
VD(DC)	DC off-state voltage <sup>+</sup>	2500		V

<sup>+</sup> : V<sub>GK</sub> = -2V

Symbol	Parameter	Conditions	Ratings	Unit
ITQRM	Repetitive controllable on-state current	V <sub>DM</sub> = 4500V, T <sub>j</sub> = 125°C, C <sub>s</sub> = 3.0μF, L <sub>s</sub> = 0.25μH	3000	A
IT(RMS)	RMS on-state current		1600	A
IT(AV)	Average on-state current	f = 60Hz, sine wave θ = 180°, T <sub>f</sub> = 78°C	1000	A
ITSM	Surge (non-repetitive) on-state current	One half cycle at 60Hz	20	kA
I <sup>2</sup> t	Current-squared, time integration	One cycle at 60Hz	1.7 × 10 <sup>6</sup>	A <sup>2</sup> s
diT/dt	Critical rate of rise of on-state current	V <sub>D</sub> = 3400V, I <sub>GM</sub> = 25A, T <sub>j</sub> = 125°C	500	A/μs
VFGM	Peak forward gate voltage		10	V
VRGM	Peak reverse gate voltage		19	V
IFGM	Peak forward gate current		130	A
IRGM	Peak gate reverse current		1100	A
PFGM	Peak forward gate power dissipation		520	W
PRGM	Peak reverse gate power dissipation		33	kW
PFG(AV)	Average forward gate power dissipation		130	W
PRG(AV)	Average reverse gate power dissipation		300	W
T <sub>j</sub>	Junction temperature		-40 ~ +125	°C
T <sub>stg</sub>	Storage temperature		-40 ~ +150	°C
—	Mounting force required	Recommended value 38	32 ~ 40	kN
—	Weight	Standard value	1600	g





**FG4000BX-90DA**

HIGH POWER INVERTER USE  
PRESS PACK TYPE

**ELECTRICAL CHARACTERISTICS**

Symbol	Parameter	Test conditions	Limits			Unit
			Min	Typ	Max	
V <sub>TM</sub>	On-state voltage	T <sub>j</sub> = 125°C, I <sub>TM</sub> = 3000A, Instantaneous measurement	—	—	3.8	V
I <sub>RRM</sub>	Repetitive peak reverse current	T <sub>j</sub> = 125°C, V <sub>RRM</sub> Applied	—	—	100	mA
I <sub>DRM</sub>	Repetitive peak off-state current	T <sub>j</sub> = 125°C, V <sub>DRM</sub> Applied, V <sub>GK</sub> = -2V	—	—	150	mA
I <sub>RG</sub>	Reverse gate current	T <sub>j</sub> = 125°C, V <sub>RG</sub> = 19V	—	—	100	mA
dv/dt	Critical rate of rise of off-state voltage	T <sub>j</sub> = 125°C, V <sub>D</sub> = 2250V, V <sub>GK</sub> = -2V	1000	—	—	V/μs
t <sub>gt</sub>	Turn-on time	T <sub>j</sub> = 125°C, I <sub>TM</sub> = 3000A, I <sub>GM</sub> = 25A, V <sub>D</sub> = 3400V	—	—	6	μs
t <sub>gq</sub>	Turn-off time	T <sub>j</sub> = 125°C, I <sub>TM</sub> = 3000A, V <sub>DM</sub> = 4500V, diGQ/dt = -40A/μs V <sub>RG</sub> = 17V, C <sub>S</sub> = 3.0μF, L <sub>S</sub> = 0.25μH	—	—	30	μs
I <sub>GQM</sub>	Peak gate turn-off current		—	750	—	A
V <sub>GT</sub>	Gate trigger voltage	DC METHOD : V <sub>D</sub> = 24V, R <sub>L</sub> = 0.1Ω, T <sub>j</sub> = 25°C	—	—	1.5	V
I <sub>GT</sub>	Gate trigger current		—	—	3200	mA
R <sub>th(j-f)</sub>	Thermal resistance	Junction to fin	—	—	0.012	°C/W

**PERFORMANCE CURVES**




www.BDTIC.com/MITSUBISHI


**FG4000BX-90DA**

HIGH POWER INVERTER USE  
PRESS PACK TYPE


**MAXIMUM ON-STATE POWER DISSIPATION CHARACTERISTICS (SINGLE-PHASE HALF WAVE)**




**ALLOWABLE FIN TEMPERATURE VS. AVERAGE ON-STATE CURRENT (SINGLE-PHASE HALF WAVE)**




**MAXIMUM ON-STATE POWER DISSIPATION CHARACTERISTICS (RECTANGULAR WAVE)**




**ALLOWABLE FIN TEMPERATURE VS. AVERAGE ON-STATE CURRENT (RECTANGULAR WAVE)**



**GATE TRIGGER CURRENT VS. JUNCTION TEMPERATURE (TYPICAL)**









**TURN ON TIME, TURN ON DELAY TIME VS. TURN ON GATE CURRENT (TYPICAL)**



www.BDTIC.com/MITSUBISHI

**FG4000BX-90DA**

HIGH POWER INVERTER USE  
PRESS PACK TYPE



www.BDTIC.com/MITSUBISHI