

PM200DVA120

FLAT-BASE TYPE
INSULATED PACKAGE

PM200DVA120



FEATURE

- 1φ 200A, 1200V Current-sense IGBT for 20kHz switching
- Monolithic gate drive & protection logic
- Detection, protection & status indication circuits for over-current, short-circuit, over-temperature & under-voltage (P-Fo available from upper leg devices)
- Acoustic noise-less 37kW class inverter application
- UL Recognized
Yellow Card No. E80276(N)
File No. E80271



APPLICATION

General purpose inverter, servo drives and other motor controls

PACKAGE OUTLINES

Dimensions in mm

www.BDTIC.com/MITSUBISHI




TERMINAL CODE

- | | |
|-----|-------|
| 5 | : FNO |
| 4 | : VNC |
| N 3 | : CNI |
| 2 | : SNR |
| 1 | : VN1 |
| 5 | : FPO |
| 4 | : VPC |
| P 3 | : CPI |
| 2 | : SPR |
| 1 | : VP1 |

PM200DVA120

FLAT-BASE TYPE
INSULATED PACKAGE



www.BDTIC.com/MITSUBISHI

MAXIMUM RATINGS (Tj = 25°C unless otherwise noted)

INVERTER PART

Symbol	Parameter	Condition	Ratings	Unit
VCES	Collector-Emitter Voltage	V _D = 15V, V _{CIN} = 5V	1200	V
±IC	Collector Current	T _c = 25°C	200	A
±ICP	Collector Current (Peak)	T _c = 25°C	400	A
Pc	Collector Dissipation	T _c = 25°C	1033	W
Tj	Junction Temperature		-20 ~ +150	°C

CONTROL PART

Symbol	Parameter	Condition	Ratings	Unit
V _D	Supply Voltage	Applied between : VP1-VPC, VN1-VNC	20	V
V _{CIN}	Input Voltage	Applied between : CPI-VPC, CNI-VNC	10	V
V _{FO}	Fault Output Supply Voltage	Applied between : FPO-VPC, FNO-VNC	20	V
I _{FO}	Fault Output Current	Sink current at FPO, FNO terminal	20	mA


PM200DVA120

FLAT-BASE TYPE
INSULATED PACKAGE

TOTAL SYSTEM

Symbol	Parameter	Condition	Ratings	Unit
VCC(PROT)	Supply Voltage Protected by SC	V _D = 13.5 ~ 16.5V, Inverter Part, T _j = 125°C Start	800	V
VCC(surge)	Supply Voltage (Surge)	Applied between : C1-E2, Surge value or without switching	1000	V
T _c	Module Case Operating Temperature	(Note-1)	-20 ~ +100	°C
T _{stg}	Storage Temperature		-40 ~ +125	°C
V _{iso}	Isolation Voltage	60Hz, Sinusoidal, Charged part to Base, AC 1 min.	2500	V _{rms}

(Note-1) T_c measurement point is below. (3mm depth at the center of the side of base plate)



ELECTRICAL CHARACTERISTICS (T_j = 25°C, unless otherwise noted)

INVERTER PART

Symbol	Parameter	Test Condition	Limits			Unit
			Min.	Typ.	Max.	
V _{CE(sat)}	Collector-Emitter Saturation Voltage	V _D = 15V, I _C = 200A T _j = 25°C	—	2.5	3.30	V
V _{EC}	FWDI Forward Voltage	V _{CIN} = 0V -I _C = 200A, V _D = 15V, V _{CIN} = 5V T _j = 25°C	—	2.0	3.25	V
t _{on}	Switching Time	V _D = 15V, V _{CIN} = 0V↔5V V _{CC} = 600V, I _C = 200A T _j = 125°C Inductive Load (upper and lower arm)	0.4	0.9	2.3	μs
t _{tr}			—	0.2	0.3	
t _{c(on)}			—	0.4	1.0	
t _{off}			—	2.4	3.4	
t _{c(off)}			—	0.7	1.2	
ICES	Collector-Emitter Cutoff Current	V _{CE} = V _{CES} , V _{CIN} = 15V	T _j = 25°C		1	mA
		T _j = 125°C		10		

CONTROL PART

Symbol	Parameter	Test Condition	Limits			Unit		
			Min.	Typ.	Max.			
I _D	Circuit Current	V _D = 15V, V _{CIN} = 5V	VN1-VNC		—	mA		
		VP1-VPC		—				
V _{th(ON)}	Input ON Threshold Voltage	Applied between : CPI-VPC, CNI -VNC	1.2	1.5	1.8	V		
V _{th(OFF)}	Input OFF Threshold Voltage		1.7	2.0	2.3			
SC	Short Circuit Trip Level	-20 ≤ T _j ≤ 125°C, V _D = 15V	240	—	—	A		
t _{off(SC)}	Short Circuit Current Delay Time	V _D = 15V	—	10	—	μs		
OT	Over Temperature Protection (Lower-arms only)	Base-plate Temperature detection, V _D = 15V	Trip level	111	118	125	°C	
OT _r			Reset level	—	100	—		
UV	Supply Circuit Under-Voltage Protection	-20 ≤ T _j ≤ 125°C	Trip level	11.5	12.0	12.5	V	
UV _r			Reset level	—	12.5	—		
I _{FO(H)}	Fault Output Current	V _D = 15V, V _{FO} = 15V	(Note-2)		0.01	mA		
I _{FO(L)}					10		15	
t _{FO}	Minimum Fault Output Pulse Width	V _D = 15V	(Note-2)		1.0	1.8	—	ms
V _{SXR}	SXR Terminal Output Voltage	-20 ≤ T _j ≤ 125°C, R _{in} = 6.8kΩ	4.5	5.1	5.6	V		

(Note-2) Fault output is given only when the internal SC, OT & UV protection.
 Fault output of OT protection operate by lower arm
 Fault output of OT, UV protection given pulse while over level.

PM200DVA120FLAT-BASE TYPE
INSULATED PACKAGE**THERMAL RESISTANCES**

Symbol	Parameter	Test Condition	Limits			Unit
			Min.	Typ.	Max.	
R _{th(j-c)Q}	Junction to case Thermal Resistances	Inverter IGBT part (per 1/2 module)	—	—	0.121	°C/W
R _{th(j-c)F}		Inverter FWDI part (per 1/2 module)	—	—	0.18	
R _{th(c-f)}	Contact Thermal Resistance	Case to fin, Thermal grease applied (per 1/2 module)	—	—	0.075	

MECHANICAL RATINGS AND CHARACTERISTICS

Symbol	Parameter	Test Condition	Limits			Unit
			Min.	Typ.	Max.	
—	Mounting torque	Mounting part screw : M6	3.92	4.90	5.88	N • m
—	Mounting torque	Main terminal screw : M6	3.92	4.90	5.88	N • m
—	Weight		—	510	—	g

RECOMMENDED CONDITIONS FOR USE

Symbol	Parameter	Test Condition	Recommended value	Unit
V _{CC}	Supply Voltage	Applied across C1-E2 terminals	≤ 800	V
V _D	Control Supply Voltage	Applied between : V _{P1} -V _{PC} , V _{N1} -V _{NC} (Note-3)	15 ± 1.5	V
V _{CIN(ON)}	Input ON Voltage	Applied between : C _{P1} -V _{PC} , C _{N1} -V _{NC}	≤ 0.8	V
V _{CIN(OFF)}	Input OFF Voltage		≥ 4.0	
t _{dead}	Arm Shoot-through Blocking Time	For IPM's each input signals	≥ 3.5	μs
f _{PWM}	PWM Input Frequency	Using Application Circuit input signal of IPM, 3φ Sinusoidal PWM VVVF inverter	≤ 20	kHz


(Note-1) With diode satisfying the following conditions dv/dt ≤ 1V/μs, V_{variation} ≤ 2V peak to peakwww.BDTIC.com/MITSUBISHI

PM200DVA120


FLAT-BASE TYPE
INSULATED PACKAGE

PERFORMANCE CURVES


OUTPUT CHARACTERISTICS (TYPICAL)




COLLECTOR-EMITTER SATURATION VOLTAGE CHARACTERISTICS (TYPICAL)




COLLECTOR-EMITTER SATURATION VOLTAGE CHARACTERISTICS (TYPICAL)




SWITCHING CHARACTERISTICS (TYPICAL)



DIODE FORWARD CHARACTERISTICS (TYPICAL)





DIODE REVERSE RECOVERY CHARACTERISTICS (TYPICAL)



www.BDTIC.com/MITSUBISHI

PM200DVA120

FLAT-BASE TYPE
INSULATED PACKAGE



www.BDTIC.com/MITSUBISHI