

When you need the highest quality wirewound axial terminal resistors available, choose Ohmite's 90 Series resistors.

They are manufactured by a unique process that molds the vitreous enamel over the resistive element, helping to ensure consistent dimensions. This uniformity permits 90 Series resistors to be mounted in clips, creating a heat-sinking benefit (see next page).

The durable vitreous enamel coating, which is totally lead free, permits the 90 Series resistors to maintain a hard coating while operating at high temperatures. Mechanical integrity is enhanced by the all-welded construction.

FEATURES

- Molded Construction provides consistent shape and size (Permits mounting in clips which extends power rating).
- Meets MIL-R-26 requirements for insulated resistors.
- All-welded construction.
- Flame resistant lead free vitreous enamel coating.
- Higher ratings in smaller sizes.
- Heat sink mounting clips available.

• RoHS compliant; add "E" suffix to part number to specify.

SPECIFICATIONS

Material

Coating: Molded lead free vitreous enamel.

Core: Ceramic.

Terminals: Solder-coated copper clad axial. RoHS solder composition is 96% Sn, 3.5% Ag, 0.5% Cu

Derating: Linearly from

100% @ +25°C to
0% @ +350°C.

Electrical

Tolerance: ±5%
(other tolerances available).

Power rating: Based on 25°C free air rating. (other wattages available*).

Maximum ohmic values:

See chart.

Overload:

Under 11 watts: 5 times rated wattage for 5 seconds.

11 watts: 10 times rated wattage for 5 seconds.

Temperature coefficient:

1 to 9.99Ω: ±100 ppm/°C
10Ω and over: ±30 ppm/°C

Dielectric withstand voltage:


500 VAC: 1W rating

1000 VAC: 2, 3, 5 and 11W



90 Series

Lead Free Vitreous Enamel Molded Axial Term. Wirewound, 5% Tolerance Standard



Series	Wattage*	Ohms	Dimensions (in./mm max.)		
			Length	Diam.	Voltage
91	1.5	0.1Ω-3.6K	0.452 / 11.5	0.140 / 3.6	150 24
92	2.25	0.1Ω-3.5K	0.405 / 10.3	0.219 / 5.6	85 20
93	3.25	0.1Ω-10.5K	0.577 / 14.7	0.234 / 5.9	200 20
95	5.0	0.1Ω-25K	0.968 / 24.6	0.265 / 6.7	495 20
96	6.5	0.1Ω-50K	0.952 / 24.2	0.343 / 8.7	625 20
90	11.0	0.1Ω-91K	1.811 / 46.0	0.343 / 8.7	1080 20

* 2x power ratings by using heat-sink mounting clips shown on following page.

Note: Due to space restrictions, parts are stamped with wattage ratings reduced to the nearest whole number. The actual wattage ratings are as published in this catalog.

ORDERING INFORMATION

Non-Inductive Winding
Optional (blank = std. winding)

RoHS
Compliant

91NJR10E

90 Series	Wattage	Tolerance	Resistance Value
Series-Lead	1 = 1.5W	J = 5%	1R0 = 1.00
Free Vitreous	2 = 2.25W		10R = 10.00
Enamel Molded	3 = 3.25W		250 = 250Ω
Axial Term.	5 = 5W		1K0 = 1,000Ω
Wirewound	0 = 11W		4K5 = 4,500Ω
			51K = 51,000Ω

STANDARD PART NUMBERS FOR 90 SERIES																											
Ohmic value	Wattage					Ohmic value	Wattage					Ohmic value	Wattage					Ohmic value	Wattage								
	Part No.	Prefix ▶	1.5	2.25	3.25		Part No.	Prefix ▶	1.5	2.25	3.25		Part No.	Prefix ▶	1.5	2.25	3.25	5	11	Part No.	Prefix ▶	1.5	2.25	3.25	5	11	
91 — 1R0	✓	✓	✓	✓	✓	22 — 22R	✓	✓	✓	✓	✓	350 — 350	✓	✓	✓	✓	✓	✓	3,500 — 3K5	✓	✓	✓	✓	✓	13,000 — 13K	✓	✓
1.1 — 1R1	✓	✗	✓	✓	✓	24 — 24R	✗	✓	✓	✓	✓	360 — 360	✓	✓	✓	✓	✓	✓	3,600 — 3K6	✓	✓	✓	✓	✓	14,000 — 14K	✓	✓
1.2 — 1R2	✓	✓	✓	✓	✓	25 — 25R	✗	✓	✓	✓	✓	390 — 390	✓	✓	✓	✓	✓	✓	3,900 — 3K9	✓	✓	✓	✓	✓	15,000 — 15K	✓	✓
1.3 — 1R3	✓	✓	✓	✓	✓	27 — 27R	✓	✓	✓	✓	✓	400 — 400	✓	✓	✓	✓	✓	✓	4,000 — 4K0	✓	✓	✓	✓	✓	16,000 — 16K	✓	✓
1.5 — 1R5	✓	✓	✓	✓	✓	30 — 30R	✓	✓	✓	✓	✓	430 — 430	✓	✓	✓	✓	✓	✓	4,300 — 4K3	✓	✓	✓	✓	✓	17,000 — 17K	✓	✓
1.6 — 1R6	✓	✗	✓	✓	✓	33 — 33R	✓	✓	✓	✓	✓	450 — 450	✗	✓	✓	✓	✓	✓	4,500 — 4K5	✓	✓	✓	✓	✓	18,000 — 18K	✓	✓
1.8 — 1R8	✓	✓	✓	✓	✓	35 — 35R	✓	✗	✓	✓	✓	470 — 470	✓	✓	✓	✓	✓	✓	4,700 — 4K7	✓	✓	✓	✓	✓	20,000 — 20K	✓	✓
2 — 2R0	✓	✓	✓	✓	✓	36 — 36R	✓	✗	✓	✓	✓	500 — 500	✓	✓	✓	✓	✓	✓	5,000 — 5K0	✓	✓	✓	✓	✓	22,000 — 22K	✓	✓
2.2 — 2R2	✓	✓	✓	✓	✓	39 — 39R	✓	✓	✓	✓	✓	510 — 510	✗	✓	✓	✓	✓	✓	5,100 — 5K1	✗	✓	✓	✓	✓	24,000 — 24K	✗	✓
2.4 — 2R4	✓	✗	✓	✓	✓	40 — 40R	✗	✓	✓	✓	✓	560 — 560	✓	✓	✓	✓	✓	✓	5,600 — 5K6	✓	✓	✓	✓	✓	25,000 — 25K	✓	✓
2.7 — 2R7	✓	✓	✓	✓	✓	43 — 43R	✗	✓	✓	✓	✓	600 — 600	✓	✗	✓	✓	✓	✓	6,000 — 6K0	✓	✓	✓	✓	✓	27,000 — 27K	✓	✓
3 — 3R0	✓	✓	✓	✓	✓	47 — 47R	✓	✓	✓	✓	✓	620 — 620	✓	✗	✓	✓	✓	✓	6,200 — 6K2	✓	✓	✓	✓	✓	30,000 — 30K	✓	✓
3.3 — 3R3	✓	✓	✓	✓	✓	50 — 50R	✓	✓	✓	✓	✓	680 — 680	✓	✓	✓	✓	✓	✓	6,800 — 6K8	✓	✓	✓	✓	✓	33,000 — 33K	✓	✓
3.6 — 3R6	✓	✗	✓	✓	✓	51 — 51R	✗	✓	✓	✓	✓	700 — 700	✗	✓	✓	✓	✓	✓	7,000 — 7K0	✓	✓	✓	✓	✓	35,000 — 35K	✓	✓
3.9 — 3R9	✓	✓	✓	✓	✓	56 — 56R	✓	✓	✓	✓	✓	750 — 750	✓	✓	✓	✓	✓	✓	7,500 — 7K5	✓	✓	✓	✓	✓	36,000 — 36K	✓	✓
4 — 4R0	✓	✓	✓	✓	✓	62 — 62R	✓	✓	✓	✓	✓	800 — 800	✓	✗	✓	✓	✓	✓	8,000 — 8K0	✓	✓	✓	✓	✓	39,000 — 39K	✓	✓
4.3 — 4R3	✓	✗	✓	✓	✓	68 — 68R	✓	✓	✓	✓	✓	820 — 820	✓	✓	✓	✓	✓	✓	8,200 — 8K2	✓	✓	✓	✓	✓	40,000 — 40K	✓	✓
4.7 — 4R7	✓	✓	✓	✓	✓	75 — 75R	✓	✓	✓	✓	✓	900 — 900	✗	✓	✓	✓	✓	✓	9,000 — 9K0	✓	✓	✓	✓	✓	43,000 — 43K	✓	✓
5 — 5R0	✓	✓	✓	✓	✓	82 — 82R	✓	✓	✓	✓	✓	910 — 910	✗	✓	✓	✓	✓	✓	9,100 — 9K1	✓	✓	✓	✓	✓	45,000 — 45K	✓	✓
5.1 — 5R1	✗	✓	✓	✓	✓	91 — 91R	✓	✗	✓	✓	✓	1,000 — 1K0	✓	✓	✓	✓	✓	✓	10,000 — 10K	✓	✓	✓	✓	✓	47,000 — 47K	✓	✓
5.6 — 5R6	✓	✓	✓	✓	✓	100 — 100	✓	✓	✓	✓	✓	1,100 — 1K1	✗	✓	✓	✓	✓	✓	11,000 — 11K	✓	✗	✓	✓	✓	50,000 — 50K	✓	✓
6.2 — 6R2	✓	✓	✓	✓	✓	110 — 110	✓	✓	✓	✓	✓	1,200 — 1K2	✓	✓	✓	✓	✓	✓	12,000 — 12K	✓	✓	✓	✓	✓	51,000 — 51K	✓	✓
6.8 — 6R8	✓	✗	✓	✓	✓	120 — 120	✓	✓	✓	✓	✓	1,300 — 1K3	✓	✓	✓	✓	✓	✓									
7.5 — 7R5	✓	✓	✓	✓	✓	130 — 130	✗	✓	✓	✓	✓	1,400 — 1K4	✗	✓	✓	✓	✓	✓									
8.2 — 8R2	✓	✓	✓	✓	✓	150 — 150	✓	✓	✓	✓	✓	1,500 — 1K5	✓	✓	✓	✓	✓	✓									
9.1 — 9R1	✗	✓	✓	✓	✓	160 — 160	✓	✗	✓	✓	✓	1,600 — 1K6	✗	✓	✓	✓	✓	✓									
10 — 10R	✓	✓	✓	✓	✓	180 — 180	✓	✓	✓	✓	✓	1,800 — 1K8	✓	✓	✓	✓	✓	✓									
11 — 11R	✗	✓	✓	✓	✓	200 — 200	✓	✓	✓	✓	✓	2,000 — 2K0	✓	✓	✓	✓	✓	✓									
12 — 12R	✓	✓	✓	✓	✓	220 — 220	✓	✓	✓	✓	✓	2,200 — 2K2	✓	✓	✓	✓	✓	✓									
13 — 13R	✗	✓	✓	✓	✓	240 — 240	✗	✓	✓	✓	✓	2,400 — 2K4	✓	✓	✓	✓	✓	✓									
15 — 15R	✓	✓	✓	✓	✓	250 — 250	✓	✓	✓	✓	✓	2,500 — 2K5	✓	✓	✓	✓	✓	✓									
16 — 16R	✓	✗	✓	✓	✓	270 — 270	✓	✓	✓	✓	✓	2,700 — 2K7	✗	✓	✓	✓	✓	✓									
18 — 18R	✓	✓	✓	✓	✓	300 — 300	✓	✓	✓	✓	✓	3,000 — 3K0	✓	✓	✓	✓	✓	✓									
20 — 20R	✓	✓	✓	✓	✓	330 — 330	✓	✓	✓	✓	✓	3,300 — 3K3	✓	✓	✓	✓	✓	✓									

✓ = Standard values
✗ = Non-standard values subject to minimum handling charge per item

Shaded values involve very fine resistance wire and should not be used in critical applications without burn-in and/or thermal cycling.

Check product availability at www.ohmite.com

Mounting Clip

For 90 Series



FEATURES

- Prevents severe vibration or mechanical shock to resistor
- Increases resistor wattage up to 100% when mounted on metal surface (1.5 sq. in. by 0.040 in. thick min. per watt dissipated)
- Holes in clip base permit fastening to chassis surface with machine screws, eyelets or rivets
- Sold in bags of ten (10)

STANDARD PART NUMBERS FOR 90 SERIES MOUNTING CLIP

Part No.	Resistor rating (watts)	Clip length (in./mm)	Clip width (in./mm)	Clip height (in./mm)	No. of holes	Hole centers (in./mm)	Hole diameter (in./mm)
✓ 5900	1.5	0.40 / 10.319	0.150 / 3.810	0.250 / 6.350	1		0.71 / 1.803
✓ 5902	2.25	0.35 / 8.890	0.217 / 5.500	0.275 / 6.980	2	0.156 / 3.969	0.71 / 1.803
⊕ 5904	3.25	0.50 / 12.700	0.257 / 6.500	0.319 / 8.103	2	0.250 / 6.350	0.093 / 2.362
⊕ 5906	5.0	0.90 / 22.860	0.237 / 6.019	0.284 / 7.214	2	0.400 / 10.160	0.103 / 2.616
⊕ 5908	11.0	1.75 / 44.450	0.333 / 8.458	0.377 / 9.576	2	0.800 / 20.320	0.103 / 2.616

⊕ = Most popular standard values

✓ = Standard values

⊕ = Non-standard values subject to minimum handling charge per item