

Package: S-20




Features

- Frequency Range 5 MHz to 1200 MHz
- Low Cost and RoHS Compliant
- Industry Standard SMT package
- Available in Tape-and-Reel
- 75Ω Characteristic Impedance
- Flux Coupled

Applications

- Broadband/CATV
- Wireless



Schematic

Product Description

The RFXF5743 Transformer is designed for applications that require small, low cost, and highly reliable surface mount components. Applications may be found in broadband, wireless, and other communications systems. These units are built Lead-Free and RoHS compliant. S-Parameters are available on request.

Optimum Technology Matching® Applied

- | | | | |
|--------------------------------------|--------------------------------------|-------------------------------------|------------------------------------|
| <input type="checkbox"/> GaAs HBT | <input type="checkbox"/> SiGe BiCMOS | <input type="checkbox"/> GaAs pHEMT | <input type="checkbox"/> GaN HEMT |
| <input type="checkbox"/> GaAs MESFET | <input type="checkbox"/> Si BiCMOS | <input type="checkbox"/> Si CMOS | <input type="checkbox"/> BiFET HBT |
| <input type="checkbox"/> InGaP HBT | <input type="checkbox"/> SiGe HBT | <input type="checkbox"/> Si BJT | <input type="checkbox"/> LDMOS |

RF MICRO DEVICES®, RFMD®, Optimum Technology Matching®, Enabling Wireless Connectivity™, PowerStar®, POLARIS™ TOTAL RADIO™ and UltimateBlue™ are trademarks of RFMD, LLC. BLUETOOTH is a trademark owned by Bluetooth SIG, Inc., U.S.A. and licensed for use by RFMD. All other trade names, trademarks and registered trademarks are the property of their respective owners. ©2006, RF Micro Devices, Inc.

Absolute Maximum Ratings

Parameter	Rating	Unit
RF Power	2	W
Operating Temperature	-45 to +85	°C
Storage Temperature	-55 to +100	°C



Caution! ESD sensitive device.

Exceeding any one or a combination of the Absolute Maximum Rating conditions may cause permanent damage to the device. Extended application of Absolute Maximum Rating conditions to the device may reduce device reliability. Specified typical performance or functional operation of the device under Absolute Maximum Rating conditions is not implied.


The information in this publication is believed to be accurate and reliable. However, no responsibility is assumed by RF Micro Devices, Inc. ("RFMD") for its use, nor for any infringement of patents, or other rights of third parties, resulting from its use. No license is granted by implication or otherwise under any patent or patent rights of RFMD. RFMD reserves the right to change component circuitry, recommended application circuitry and specifications at any time without prior notice.




RoHS (Restriction of Hazardous Substances): Compliant per EU Directive 2002/95/EC.

Parameter	Specification			Unit	Condition
	Min.	Typ.	Max.		
Overall					Typical values represent Mid-Band performance at 25 °C
Frequency Range	5		1200	MHz	
Insertion Loss < 1dB	5		300	MHz	
Insertion Loss < 2dB	5		1200	MHz	
Insertion Loss < 3dB				MHz	
Amplitude Balance 5MHz to 500MHz		0.3	0.5	dB	
Amplitude Balance 5MHz to 1200MHz		0.5	1.5	dB	
Phase Balance 5MHz to 500MHz		1	2	°	Nominal Phase Difference is 180°
Phase Balance 5MHz to 1200MHz		2	15	°	Nominal Phase Difference is 180°
Impedance Ratio	1:3				
Type - Flux Coupled	Unbalance to Balanced				


Input Return Loss




Insertion Loss



Amplitude Balance



Phase Balance





Pin Names and Description



Pin	Function	Description
1	Primary Dot	Input.
2	Secondary CT	Ground.
3	Primary	Ground.
4	Secondary	Output 2.
5	Secondary Dot	Output 1.

Package Drawing - S20

Dimensions in inches (millimeters)



PCB FOOTPRINT



Ordering Information

Ordering Code	Description	Reel Size	Package
RFXF5743SB	5MHz to 1200MHz 1:3 SMT Transformer	N/A	5-Piece bag
RFXF5743SQ	5MHz to 1200MHz 1:3 SMT Transformer	N/A	25-Piece bag
RFXF5743SR	5MHz to 1200MHz 1:3 SMT Transformer	13"	100-Piece reel
RFXF5743TR13	5MHz to 1200MHz 1:3 SMT Transformer	13"	1000-Piece reel