



VCO Product Specification

Model: VCO790-1550TY **Rev:** A **Date:** 8/10/2009
Customer: RF MICRO DEVICES
Operating Temperature Range: (-40 ° to 85 ° C)

RoHS Compliant

Parameter	Min	Typ	Max	Units	X	Remarks
Frequency Range -	950		2150	MHz	X	
Tuning Voltage:						
950 MHz	0.5	1.4		Vdc	X	***
2150 MHz		19	22	Vdc	X	
Tuning Sensitivity:						
950 MHz	60	80	100	MHz/V	X	
1250 MHz	50	70	90	MHz/V	X	
1550 MHz	55	75	95	MHz/V	X	
1850 MHz	45	65	85	MHz/V	X	
2150 MHz	35	55	75	MHz/V	X	
Output Power -	3	6	9	dBm	X	
Output Phase Noise:						
1 kHz		-70	-65	dBc/Hz		
10 kHz		-98	-93	dBc/Hz		
100 kHz		-118	-113	dBc/Hz	X	
1000 kHz		-138	-133	dBc/Hz		
Power Supply -	4.75	5	5.25	Volts	X	
Supply Current -		25	30	mA	X	
Harmonic Suppression:						
2nd Harmonic		-8	-4	dBc	X	
3rd Harmonic		-18	-10	dBc	X	
Spurious (Non-Harmonic) -			-80	dBc		
Frequency Pushing - 4.75 - 5.25 V		2.5	5	MHz p-p	X	
Frequency Pulling - into a 12 dB RL		10	15	MHz p-p	X	
Tuning Port Capacitance -		100		pF		
Output Impedance -		50		Ω		

Package Information

Package Type:	T (0.5 x 0.5 x 0.156 inches)	Drawing Number:	60035
---------------	------------------------------	-----------------	-------

Comments

X Indicates parameter to be tested 100% in production

*** Tuning Curve is monotonic form $V_t=0$ V dc to V_{tmax} and is guaranteed to oscillate at $V_t=0$ Vdc

RoHS status based on EU Directive 2002/95/EC (at time of this document revision).

The information in this publication is believed to be accurate and reliable. However, no responsibility is assumed by RF Micro Devices, Inc. ("RFMD") for its use, nor for any infringement of patents, or other rights of third parties, resulting from its use. No license is granted by implication or otherwise under any patent or patent rights of RFMD. RFMD reserves the right to change component circuitry, recommended application circuitry and specifications at any time without prior notice.