



VCO Product Specification

Model: VCO793-750TY **Rev:** A **Date:** 8/10/2009
Customer: RF MICRO DEVICES
Operating Temperature Range: (-40 ° to 85 ° C)

RoHS Compliant

Parameter	Min	Typ	Max	Units	X	Remarks
Frequency Range -	500		1000	MHz	X	
Tuning Voltage:						
500 MHz	0	2.2		Vdc	X	
1000 MHz		18	20	Vdc	X	
Tuning Sensitivity:						
500 MHz	33	38	43	MHz/V	X	
625 MHz	33	38	43	MHz/V	X	
750 MHz	35	40	45	MHz/V	X	
875 MHz	30	39	44	MHz/V	X	
1000 MHz	24	29	34	MHz/V	X	
Output Power -	1	6	10	dBm	X	
Output Phase Noise:						
1 kHz		-79	-74	dBc/Hz		
10 kHz		-104	-99	dBc/Hz		
100 kHz		-124	-119	dBc/Hz	X	
1000 kHz		-144	-139	dBc/Hz		
Power Supply -	11.5	12	12.5	Volts	X	
Supply Current -		25	30	mA	X	
Harmonic Suppression:						
2nd Harmonic		-6		dBc	X	
3rd Harmonic		-18		dBc	X	
Spurious (Non-Harmonic) -			-80	dBc		
Frequency Pushing - 11.5-12.5 V		1.5	3	MHz p-p		
Frequency Pulling - 12 dB RL		2	5	MHz p-p		
Tuning Port Capacitance -		220		pF		
Output Impedance -		50		Ω		

Package Information

Package Type:	T (0.5 x 0.5 x 0.156 inches)	Drawing Number:	60035
---------------	------------------------------	-----------------	-------

Comments

X Indicates parameter to be tested 100% in production

*** Tuning curve is monotonic from Vt=0 Vdc to Vmax and is guaranteed to oscillate to Vt=0 Vdc

RoHS status based on EU Directive 2002/95/EC (at time of this document revision).

The information in this publication is believed to be accurate and reliable. However, no responsibility is assumed by RF Micro Devices, Inc. ("RFMD") for its use, nor for any infringement of patents, or other rights of third parties, resulting from its use. No license is granted by implication or otherwise under any patent or patent rights of RFMD. RFMD reserves the right to change component circuitry, recommended application circuitry and specifications at any time without prior notice.