









特 性

- 高密度集, 多個電阻在一個表貼封裝中
- 裝配效率高
- 編帶卷裝適合自動化機器
- 優越焊錫性



	2D02	4D02	4D03	16P8
規格 (mm)				
等效電路圖				

類型	2D02	4D02	4D03	16P8
功率 (70°C)	1/16W	1/16W	1/16W	1/16W
最大工作電壓	25V	25V	50V	50V
最大過負荷電壓	50V	50V	100V	100V
絕緣耐壓	100V	100V	300V	300V
阻值範圍	5% (E-24): 10Ω~1MΩ 1% (E-96): 10Ω~1MΩ	5% (E-24): 10Ω~1MΩ 1% (E-96): 10Ω~1MΩ	5% (E-24): 1Ω~1MΩ 1% (E-96): 1Ω~1MΩ	5% (E-24): 1Ω~1MΩ 1% (E-96): 1Ω~1MΩ
溫度系數	±200PPM/°C	±200PPM/°C	≥10Ω: ±200PPM/°C <10Ω: ±400PPM/°C	≥10Ω: ±200PPM/°C <10Ω: ±400PPM/°C
工作溫度範圍	-55°C~+155 °C	-55°C~+155 °C	-55°C~+155 °C	-55°C~+155 °C
零歐姆電阻阻值	<50mΩ	<50mΩ	<50mΩ	<50mΩ
零歐姆電阻額定電流	1A	1A	1A	1A

性 能

短時間過負荷	±(2.0% ±0.1Ω) 最大
絕緣電阻	≥1,000 Mega Ohm.
絕緣耐壓	無擊穿, 飛弧及可見機械性損傷
端子強度	±(1.0% ±0.05Ω) 最大
耐焊接熱	電阻值變化率 ±(1.0% ±0.05Ω) 最大
可焊性	最少 95% 覆蓋
溫度循環	ΔR/R ≤ ±(1.0% ±0.05Ω)
濕度壽命	±(3.0% ±0.1Ω) 最大
負載壽命	±(3.0% ±0.1Ω) 最大

- 訂購方式, 請參考第 4 頁 (料號)